AIRMASTER®
ventilation in balance

Nomenclature / Plate System Airmaster Products AM 300

AM 300 HHBB-WCH,B1

Series:
AM

Type:
300

Version:

1. Character:
H – Horizontal Exhaust
V – Vertical Exhaust
S – Side Exhaust

2. Character
H – Horizontal Supply
V – Vertical Supply
S – Side Supply

3. Character
B – Inlet Bottom
DI- Ducted Inlet

4. Character
B – Extract Bottom
DE- Ducted Extract

Options:

BP	Bypass (standard)
CP	Condensate Pump
EM	Energy Meter
ePM_{10} 50%	Supply air filter ePM_{10} 50%
ePM_1 55%	Supply air filter ePM_1 55%
ePM_1 80%	Supply air filter ePM_1 80% (special part)
CH	Comfort Heater
WCH	Water Comfort Heater
PHS	Preheating Surface
ED	Motor-driven Exhaust Air Damper
SD	Motor-driven Supply Air Damper
CO	External CO_2 Sensor
HY	External Hygrostat
ICO	Internal CO_2 Sensor
ICT	Internal CO_2-/TVOC Sensor
IPIR	Internal Motion Sensor
IT	Internal TVOC Sensor
PIR	External Motion Sensor
B1	BACnet™/IP
B2	BACnet™ MS/TP
K	KNX®
L	LON®
M	MODBUS® RTU RS485
AO	Airmaster Airlinq® Online

Airmaster A/S
Industrivej 59
DK-9600 Aars

Tel.: +45 98 62 48 22
info@airmaster.dk
www.airmaster-as.com

CVR nr.: 29 52 73 93